



Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Model Number: AUHW-80N3MA

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_



### SYSTEM PERFORMANCE DATA

<b>Power supply</b>		
Normal Operational Voltage	(V, Ph, Hz)	240V, 1Ph, 60Hz
Voltage Range	(V)	208~240
<b>Electrical</b>		
Minimum circuit ampacity	(A)	23.6A(208V)/26.8A(240V)
Max.fuse	(A)	25A(208V)/30A(240V)
Connection wiring		AWG 10-3
<b>Energy information</b>		
Normal Gallon Capacity	(Gallon)	80
Rated Gallon Capacity	(Gallon)	75
Uniform Energy Factor (UEF)		4
First Hour Rating (FHR)	(Gallon)	91
Water Outlet Temperature Range	Deg. °F (°C)	109°F~149°F (43°C~65°C)
Upper Element Wattage	(W)	4500(240V)
Lower Element Wattage	(W)	4500(240V)
Compressor capacity	(W)	1500
Total Unit Wattage (input)	(W)	5500
Cold Climate Efficiency(CCE)		3
Recovery In G.P.H. 90° F Rise		27.5
Heat pump ambient operating range	Deg. °F (°C)	37°F~109°F (3°C~43°C)
Element ambient operating range	Deg. °F (°C)	5~115(-15°C~46°C)
Sound	(dBA)	49.5

### UNIT DATA

Body Height	inch(mm)	74-1/4(1884.7)
Body Diameter(inch)	inch(mm)	25-5/8(650.2)
Body Weight	lbs(kg)	293.2(133)
Ship Length(inch)	inch(mm)	30-1/4(769.6) x 29-1/8(739.1)
Ship Height(inch)	inch(mm)	83-1/8(2110.7)
Ship Weight(lbs)	lbs(kg)	357.2(162)
Inlet Water Connection Size	inch(mm)	3/4(19.1)
Outlet Water Connection Size	inch(mm)	3/4(19.1)
Drainage Hose	inch(mm)	3/4(19.1)
Installation Clearance (Back)	inch(mm)	0
Installation Clearance (side)	inch(mm)	6(152.4)
Installation Clearance (top)	inch(mm)	20(508)
Refrigerant Type		R134a
Refrigerant charge	oz(g)	18.34(520)
Loading quantity(40HQ)	pcs	45

